PELTOR™

The Sound Solution

Smart Communication

MT20H682FB-38 SV

3M™ PELTOR™ ComTac XPI Headset

Level-dependent Hearing Protection

- **Hearing Protection**
  Noise attenuating headset helps provide hearing protection in environments with potentially hazardous noise
- **Situational Awareness**
  Level-dependent function for situational awareness and communication
- **Connectivity & Communication**
  The external radio jack or connection cable provides the possibility to connect to an external communication device
- **Easy to use**
  The headset is controlled with three buttons along with a ghost voice to help guide you through the settings

Hearing protection with level-dependent function for ambient listening

Hearing protection with external audio input

www.3M.com/PELTOR

3M

Smart **Solutions**
Easy Communication

PELTOR™

Hearing Protection
Noise attenuating ear cups help provide hearing protection in environments with potentially hazardous noise.

Stainless Steel Wire Headband
Wire headband offers comfortable and consistent pressure.

Level-dependent Microphone
Supports situational awareness and communication.

Boom Speech Microphone
Help you to communicate via radio or intercom in noisy environment.

External Connector Cable
Provides the possibility to connect direct to a communication device via a adapter.

Headset Models

3M ID	Product Description	Colour	Band Style			Microphone Type			Connector	
			Head-band	Neck-band	Helmet attachment	Standard Mic	Flex Mic	No Mic	PELTOR J11	NATO J11
XH001680988	MT20H682FB-02 SV ComTac XPI	Black	X					X		
UU001501285	MT20H682FB-38 SV ComTac XPI Headset	Black	X			X			X	
UU001501061	MT20H682BB-38 SV ComTac XPI Headset	Black		X		X			X	
UU001501301	MT20H682P3AD-38 SV ComTac XPI Headset	Black			X	X			X	
UU001501814	MT20H682FB-68 SV ComTac XPI Headset Flex Mic	Black	X				X		X	
XH001681036	MT20H682FB-86 SV ComTac XPI Headset NATO	Black	X			X				X

Articles & Accessories

Article number	Description	3M ID number
1079 SV	Battery lid	11003065544
HY68 SV	Hygiene kit (attenuation cushions & foam)	XH001654461
MT7N	Microphone, dynamic	XL001634044
MT31E/1	Flexi boom speech microphone	UU001501863
M60/2	Wind shield for attenuation mic	XH001652532

Technical data

Power:	2 x AAA 1.2-1.5V batteries
Operating time:	Approximately 200h (battery & temperature dependent)
Net Weight:	335g (inc. batteries)
Colour:	Black
Operating temperature:	-40°C to +55°C (battery dependent)
Storage Temperature:	-50°C to +70°C

MT20H682FB-* (foldable headband)
SNR=28 dB H=31 dB M=25 dB L=16 dB

MT20H682BB-* (neckband)
SNR=28 dB H=31 dB M=25 dB L=18 dB

WebHill.fi -Verkkokauppa
www.webhill.fi
info@webhill.fi

3M

3M Personal Safety Division
3M Svenska AB, Box 2341
SE-331 02 Värnamo
Sweden
Internet: www.3M.com/PELTOR

Please recycle. Printed in Sweden.
© 3M 2015. All rights reserved.
3M is a trademark of 3M Company, used under license in Canada.
PELTOR is a trademark of 3M Svenska AB, used under license in Canada.

P158366 rev. a 3M™ PELTOR™ Global Marketing Communication, Värnamo